

Touch Industrial PC VESA 15.6

Datasheet

- Panel
- System
- Interfaces
- Power Supply
- Mechanical & Environmental
- Ordering Information



Panel

LCD Size	15.6 inch (39.6 cm)
Resolution	1920 x 1080
Aspect Ratio	16 : 9
Technology	TFT
Colours	16.7 M
Backlight	LED
Backlight Life Time	50,000 h
Luminance*	450 cd/m ²
Contrast Ratio*	800 : 1
Viewing Angle* (right/left/up/down)	89°/89°/89°/89°
Touch	Projected Capacitive Touch, Multitouch, Anti-Glare

*The values are referring to the display only.

System



CPU	Intel® Core™ i5-1145G7E 1.5/4.1 GHz
Graphic	Intel® Iris® Xe
Memory	16 GB DDR4
Storage	512 GB 3D TLC SSD
BIOS	AMI Optio 5 BIOS
Wake on LAN	Yes
H/W Status Monitoring	Supports Power Supply Voltage and Temperature Monitoring
CMOS Battery	Lithium Battery (CR2450/610 mAh)
RTC	Internal RTC
TPM	TPM 2.0 (SLB9670)
Watchdog	Yes
RAID	No

Touch Industrial PC VESA 15.6

Datasheet

Interfaces

Power	1 x Phoenix 3-pin MC 1,5/ 3-STF-3,5 BK (screwable), PWR X11
USB	2 x USB Host 3.2 Gen 1 (Type A), X33, X34 2 x USB Host 2.0 (Type A), X31, X32 1 x USB Host 2.0 (Type A), side
Network	3 x 2.5 Gbit Ethernet (RJ45), ETH X21, ETH X22, ETH X23
Serial	1 x RS-232 / RS-485 / RS-422 (Sub-D) (BIOS setting), Serial X41
Video	1 x DisplayPort 1.4, DP X71



PWR X11

PIN	Signal
1	Ground
2	Functional Earth
3	24 VDC \pm 20 %

Serial X41

PIN	RS-232	RS-422	RS-485
1	DCD	TX-	Data-
2	RX	TX+	Data+
3	TX	RX+	--
4	DTR	RX-	--
5	Ground	Ground	Ground
6	DSR	--	--
7	RTS	--	--
8	CTS	--	--
9	RI	--	--

Touch Industrial PC VESA 15.6

Datasheet

Power Supply

Supply Voltage	24 VDC \pm 20 %
Power Consumption (max*)	up to 70 W
Power Button	Yes (left side)
Power Connector	Phoenix 3-pin MC 1,5/ 3-STF-3,5 BK (screwable), PWR X11
Fuse	6 A, time lag, non-exchangeable

*max. periphery consumption included (e.g. 1 x USB 2.0 equals 2.5 W)

Mechanical & Environmental

Housing Front	Glass, black frame
Housing	Aluminium / silver / black
Dimensions	412 x 256 x 61 [mm]
Mounting	VESA MIS-D, 75 / VESA MIS-D, 100
Weight	Without IP cover: max. 4.0 kg With IP cover: additional 0.5 kg
Cooling	Passive
Ambient Temperature	0 ~ 50 °C
Storage Temperature	-10 ~ 70 °C
Humidity	5 ~ 80 % (non condensing)
Protection Class	Without IP cover: IP65 (IP20 rear) With IP cover: IP65
Certification	CE, EN55032 Class A, EN55035

Never cover the Touch Industrial PC VESA 15.6 completely on the back or build it in a small closed and unvented housing.

Detailed size information can be found in the technical drawing under the following link:

[Technical drawing VESA 15.6](#)

Find the assembly guide for the IP cover under the following link:

[IP cover assembly guide](#)

Touch Industrial PC VESA 15.6

Datasheet

Ordering Information

Ordering-No.	
PA10014011	Touch Industrial PC VESA 15.6
PA10015242	IP cover

Datasheet valid from device revision 2.

Disclaimer

Christ Electronic Systems GmbH reserves the right to change the information, designs and technical data contained in this documentation without prior notice, as the products are subject to constant further development. No guarantee is given that the data is complete, up-to-date and correct. In this document, all brand names as well as software and hardware designations used are subject to the respective companies, general trademark, brand or patent protection.

Contact

Christ Electronic Systems GmbH
Alpenstraße 34
87700 Memmingen

Phone:
+49 8331 8371-0 (Main Office)
+49 8331 8371-500 (Service)

Mail:
info@christ-es.de

Homepage:
<https://www.christ-es.com>

© Christ Electronic Systems GmbH