

# Touch Industrial PC Front Panel 10.1

## Datasheet

- Panel
- System
- Interfaces
- Power Supply
- Mechanical & Environmental
- Ordering Information



### Panel

LCD Size	10.1 inch (25.7 cm)
Resolution	1280 x 800
Aspect Ratio	16 : 10
Technology	TFT
Colours	16.2M
Backlight	LED
Backlight Life Time	50,000 h
Luminance*	500 cd/m <sup>2</sup>
Contrast Ratio*	800 : 1
Viewing Angle* (right/left/up/down)	89°/89°/89°/89°
Touch	Projected Capacitive Touch, Multitouch, Anti-Glare

\*The values are referring to the display only.

### System



CPU	Intel® Core™ i5-1145G7E 1.5/4.1 GHz
Graphic	Intel® Iris® Xe
Memory	16 GB DDR4
Storage	512 GB 3D TLC SSD
BIOS	AMI Optio 5 BIOS
Wake on LAN	Yes
H/W Status Monitoring	Supports Power Supply Voltage and Temperature Monitoring
CMOS Battery	Lithium Battery (CR2450/610 mAh)
RTC	Internal RTC
TPM	TPM 2.0 (SLB9670)
Watchdog	Yes
RAID	No

# Touch Industrial PC Front Panel 10.1

## Datasheet

### Interfaces

<b>Power</b>	1 x Phoenix 3-pin MC 1,5/ 3-STF-3,5 BK (screwable), PWR X11
<b>USB</b>	2 x USB Host 3.2 Gen 1 (Type A), X33, X34 2 x USB Host 2.0 (Type A), X31, X32 1 x USB Host 2.0 (Type A), side
<b>Network</b>	3 x 2.5 Gbit Ethernet (RJ45), ETH X21, ETH X22, ETH X23
<b>Serial</b>	1 x RS-232 / RS-485 / RS-422 (Sub-D) (BIOS setting), Serial X41
<b>Video</b>	1 x DisplayPort 1.4, DP X71



#### PWR X11

PIN	Signal
1	Ground
2	Functional Earth
3	24 VDC $\pm$ 20 %

#### Serial X41

PIN	RS-232	RS-422	RS-485
1	DCD	TX-	Data-
2	RX	TX+	Data+
3	TX	RX+	--
4	DTR	RX-	--
5	Ground	Ground	Ground
6	DSR	--	--
7	RTS	--	--
8	CTS	--	--
9	RI	--	--

# Touch Industrial PC Front Panel 10.1

## Datasheet

### Power Supply

<b>Supply Voltage</b>	24 VDC $\pm$ 20 %
<b>Power Consumption (max*)</b>	up to 55 W
<b>Power Button</b>	No
<b>Power Connector</b>	Phoenix 3-pin MC 1,5/ 3-STF-3,5 BK (screwable), PWR X11
<b>Fuse</b>	6.3 A, time lag, non-exchangeable

\*max. periphery consumption included (e.g. 1 x USB 2.0 equals 2.5 W)

### Mechanical & Environmental

<b>Housing Front</b>	Glass, black frame
<b>Housing</b>	Aluminium / silver / black
<b>Dimensions</b>	273 x 190 x 57 [mm]
<b>Cutout</b>	262 x 179 [mm] rounded corners with radius 10 mm, see technical drawing
<b>Weight</b>	max. 2.3 kg
<b>Cooling</b>	Passive
<b>Ambient Temperature</b>	0 ~ 50 °C
<b>Storage Temperature</b>	-10 ~ 70 °C
<b>Humidity</b>	5 ~ 80 % (non condensing)
<b>Protection Class</b>	IP65 (IP20 rear)
<b>Certification</b>	CE, EN55032 Class A, EN55035

Never cover the Touch Industrial PC Front Panel 10.1 completely on the back or build it in a small closed and unvented housing.

Detailed size information can be found in the technical drawing under the following link:

[Technical drawing Front Panel 10.1](#)

# Touch Industrial PC Front Panel 10.1

## Datasheet

### Ordering Information

Ordering-No.	
PA10015438	Touch Industrial PC Front Panel 10.1

Datasheet valid from device revision 0.

### Disclaimer

Christ Electronic Systems GmbH reserves the right to change the information, designs and technical data contained in this documentation without prior notice, as the products are subject to constant further development. No guarantee is given that the data is complete, up-to-date and correct. In this document, all brand names as well as software and hardware designations used are subject to the respective companies, general trademark, brand or patent protection.

### Contact

Christ Electronic Systems GmbH  
Alpenstraße 34  
87700 Memmingen

Phone:  
+49 8331 8371-0 (Main Office)  
+49 8331 8371-500 (Service)

Mail:  
info@christ-es.de

Homepage:  
<https://www.christ-es.com>

© Christ Electronic Systems GmbH